

36" OPEN BURNER RANGETOP

The Capital Chef's Collection 36" rangetop expands your culinary options. Customize the layout by replacing two of the six burners with a 12" Thermo–Griddle[™] or BBQ grill.

36" OPEN BURNER RANGETOP FEATURES

- Power-Flame[™] burners are rated at 25,000 BTUs to deliver intense powerful heat
- All burners turn down to a true simmer
- FineTouch™ simmer burner rated at 8,000 BTUs
- EZ-Clean[™] Drip Trays Full extension removable drip trays mounted on ball bearing rails
- Ergo-Cool[™] Die cast, chrome-plate ergonomic metal knobs are cool to the touch
- Auto-ignition/re-ignition on all burners
- Island trim attached

BBQ GRILL

Inclement weather doesn't have to stop your grilling. With 18,000 BTUs (12") or 36,000 BTUs (24"), this indoor grill system sears at commercial-level temperatures. Bring outdoor grilling indoors with variable temperature control on our two-sided TruSide[™] channeling grates and our hybrid ceramic radiants encased in stainless steel. All BBQ grills come with stainless steel covers.

THERMO-GRIDDLE[™]


The true breakfast of champions is cooked on a Capital; there's nothing like waking up in the morning and cracking a fresh egg over a piping hot griddle. Our 3/8" thick thermostatically controlled stainless steel griddle plate gives precise control over the griddle area, won't rust, and doesn't require pre-conditioning. All Thermo-Griddles[™] come with stainless steel covers.



RANGETOP FEATURES



OPEN BURNER Restaurant-quality performance.



BBQ GRILL Capital's indoor commercial quality grill system.




THERMO-GRIDDLE[™] Improve your indoor cooking experience and make outstanding meals on the Capital stainless steel Thermo-Griddle[™].



36" OPEN BURNER RANGETOP

MAKE ROOM FOR MORE.

OPEN BURNER RANGE CONFIGURATIONS



Capital Cooking offers customized placements of your burners, griddle, and BBQ grill. Ask your Capital dealer for details.

FINISH OPTIONS

CUTOUT DIMENSIONS

The Capital Open Burner Rangetop is available in a timeless stainless steel only with four modern knob finish options to choose from.



30, 36, 48, 60, Wide Hood REQUIRED 12" mi Δ PxxSLE all Protector Accessories (sold all-mounted with i ist be installed wh Electrical and Gas Supply Island Trims 29 7/8" 26 1/2" 23" 30" Models 8 1/4" 28" 7/12" 1/2" 2 1/2' 35 7/8" 47 7/8" 26 1/2" 26 1/2" 8 1/4" 35" 8 1/4" 46" 23" 23" 1/2" 1/2" 2 1/2" 2 1/2" 36" Models 7/12" 48" Models 7/12" All Models: Electrical: 120 VAC, 60 Hz Circuit Breaker Required: 20 Amp 60" Models 59 7/8" 26 1/2" 8 1/4" 58" 23" 7/12" 1/2" 2 1/2 ‡ Wall protector accessory sold separately GRT CGRT These must be installed when

GAS REQUIREMENTS : 1/2" NPT gas connection. Minimum gas supply is 7" water column for natural gas and 11" for propane. Operating pressure at the manifold is 5" water column for natural gas and 10" for propane. All units include a gas regulator. The installer must provide a shut-off valve at the rear of the appliance with easy access to shut off the gas for service. High-altitude kits and gas conversion kits are available through the Capital parts department.

For more details, visit our website: www.capital-cooking.com All product details and specifications are subject to change without notice.



combustible construction is present.