

HCB 2091

Fully Integrated Appliances

LIEBHERR

Refrigeration and Freezing



home.liebherr.com



HCB 2091

Energy consumption (kWh/y)	580
Estimated Yearly Energy Cost* in US \$	81
Sound rating** dB(A)	43
Refrigerator capacity cu.ft. (l)	12.9(365)
BioFresh compartment cu.ft. (l)	2.4(6.9)
Freezer capacity cu.ft. (l)	6.0(170)
Electronic control	MagicEye with digital temp. display, touch electronic
Defrost type	Automatic
Interior light	LED Light column/ LED ceiling
Number of shelves	4
Number of door racks	6
Number of BioFresh drawers	2
Number of freezer drawers	2
Refrigerator Temperature range °F (°C)	+36°F to +43°F (+2°C to +6°C)
Freezer Temperature range °F (°C)	+7°F to -17°F (-14°C to -27°C)
Water filter	yes
Ice maker	Fixed with water connection
Ice cube output lbs. (kg.)	3.1(1.4)
Ice cube stock lbs. (kg.)	6(2.7)
Door hinges	left
Product dimensions	
in inch (H/W/D)	79 13/16" / 35 7/8" / 24 1/16"
in cm (H/W/D)	202.7/91/61.5
Cut out dimensions	
in inch (H/W/D)	80"-81 5/8" / 36 1/16" / 25"
in cm (H/W/D)	203.2-207.2/91.5/63.5
Net weight lbs. (kg)	370.4 (168.0)
Voltage V/Hz	115/60

* Energy Cost will depend on utility rates and use. Estimated energy cost based on a national average electricity cost of 14 cents per KWh.

** Noise output – according to EN 60704-3

Accessories

Water Filter	9880980/7440002
Stainless Steel Round Handles	9900327
Brushed Aluminium Square Handles	9900329
Door Stopper 90*	9096699
Stainless Steel Panels Refrigerator 80"	9900333
Stainless Steel Panels Refrigerator 84"	9900331
Stainless Steel Panels Freezer Drawers	9900323

Features

- Bio Fresh** Preserve just-bought groceries for optimum food freshness, while sealing in flavors and maintaining essential vitamins and minerals.
- Duo Cooling** Lengthen the shelf life and preserve the flavor of your foods with a dual refrigeration system that creates ideal conditions in both the refrigerator and freezer.
- Ice Maker** Liebherr's automatic IceMaker produces perfect ice cubes and keeps a constant supply on hand for every occasion.
- Telescopic Rails** Store food securely within reach thanks to fully extendable pull-out drawers. The SoftTelescopic system provides convenient and reliable self-retraction with soft closing.

Diagrams

Product Dimensions

Front View Dimensions:
 Total height: 79-1/2" (2020 mm)
 Refrigerator compartment height: 33-7/8" (861 mm)
 Freezer compartment height: 20-3/16" (512.5 mm)
 Freezer door height: 14-1/2"
 Freezer door depth: 11/4"
 Freezer door depth (with handle): 11/4" + 20-3/16" (512.5 mm)

Top View Dimensions:
 Width: 35-13/16" (910 mm)
 Depth: 22-1/16" (561 mm)
 Door swing depth: 3/8"
 Hinge offset: 15"
 Hinge offset (mm): 381 mm
 Door swing angle: 90° to 115°

Side View Dimensions:
 Total height: 79-11/16" (2024 mm)
 Door height: 1-7/16" (37 mm)
 Hinge height: 1-11/16" (43 mm)
 Freezer door height: 1-7/8" (48 mm)
 Freezer door depth: 13-1/2" (343 mm)
 Freezer door depth (with handle): 3-3/4" (95 mm)

Allow door swing clearance at locations next to a wall.
 The refrigerator door must open to a minimum of 90° to allow the crispers to open and the shelves to be removed.

Height can be increased by 1-1/2" (40 mm) by turning the levelling feet at the front and the height adjustable roller units at the appliance rear.

Panel Dimensions

Inset Installation Style

Cabinet opening A: 80" or 84"
 Cabinet opening B: 35 - 3/4" (908 mm)

Frameless Installation Style

Cabinet opening A: 80" or 84"
 Cabinet opening B: 36 - 1/2" (927 mm)

Cabinet opening A	Cabinet opening B	Cabinet opening A	Cabinet opening B
80"	45-1/4" (1150 mm)	80"	45-3/4" (1162 mm)
84"	49-1/4" (1251 mm)	84"	49-3/4" (1264 mm)

Minimum panel thickness is 5/8" (16 mm).
 Maximum panel thickness is 1-1/2" (38 mm).
 Maximum weight of the refrigerator panel is 60 lbs (27 kg).
 Maximum weight of each freezer panel is 26.5 lbs (12 kg).

Cutout Dimensions

Factory available stainless steel panels are designed for an inset installation only and require a cabinet / gable depth of 24 - 3/4".

Inset cabinet Depth D
24" + panel thickness
Frameless cabinet Depth D
24"

80" or 84"
 2-3/4" (70 mm)
 7-5/8" (195 mm)
 Water line outlet
 Water supply line
 36" Single / 72" Side by Side

Ventilation Requirements

The appliance do not require ventilation considerations in the cabinetry. The required airflow is directed through the toe kick base. It is important to use the provided cover grille for the ventilation opening. This opening must not be covered.

Subject to modification. For up-to-date information, visit home.liebherr.com.
 Specifications are for planning purposes only. For more detailed information, refer to installation instructions or Design Guide.