








-  **ITAC08-KS21** 8,000 BTU
-  **ITAC10-KSA21** 10,000 BTU
-  **ITAC10-KSB21** 10,000 BTU
-  **ITAC12-KSA21** 12,000 BTU
-  **ITAC12-KSB21** 12,000 BTU
- ITAC14-KR** 14,000 BTU

Cool & Electric Heat

- ITAH-08KR** 8,000/4,200 BTU
- ITAH-12KRB** 12,000/10,600 BTU

Through The Wall Air Conditioner

COOL
FAN
DEHUMIDIFY
HEAT
(limited models)

Trim Kit Included



PROGRAMMABLE 24 HOUR DELAY

Save energy by running your AC only when you need it



ELECTRONIC/DIGITAL CONTROL

Easily regulate Mode and temperature settings on AC unit as desired



WASHABLE FILTER

Enables easy maintenance for the unit



3 COOLING SPEEDS, 3 FAN SPEEDS

Reduce noise level and save money with lowered cooling and fan settings



AUTO RESTART

Restores AC to previous settings in case of power outage



REMOTE CONTROL

Adjust and control settings at a glance



SLEEP MODE

Automatically resume previous settings when turning the unit back on



4 WAY AIR DIRECTION

Guide the air flow up or down



WHISPER QUIET OPERATION

Enjoy comfortable noise levels with our preferred units' whisper quiet operation



- ITAC08-KS21** 8,000 BTU
 - ITAC10-KSA21** 10,000 BTU
 - ITAC10-KSB21** 10,000 BTU
 - ITAC12-KSA21** 12,000 BTU
 - ITAC12-KSB21** 12,000 BTU
 - ITAC14-KR** 14,000 BTU
- Cool & Electronic Heat
- ITAH-08KR** 8,000/4,200 BTU
 - ITAH-12KRB** 12,000/10,600 BTU



Model		ITAC08-KS21	ITAC10-KSA21	ITAC10-KSB21	ITAC12-KSA21	ITAC12-KSB21	ITAC14-KR	ITAH-08KR	ITAH-12KRB	ITA-US10
Performance	Cooling Capacity (BTU/hr)	8,000	10,000	10,000/9,800	12,000	12,000/ 11,700	14,000/ 13,600	8,000	12,000/ 11,700	
	Heating Capacity (BTU/hr)	-	-	-	-	-	-	4,200	10,600/8,600	
	Application area (sq. Feet)	350	450	450	550	550	700	350	550	
	CEER	9.7	9.7	9.7	9.7	9.7	9.3	9.6	9.5	
	EER	9.8	9.8	9.8	9.8	9.8	9.3	9.6	9.5	
Electrical Ratings	Voltage	115	115	230/208	115	230/208	230/208	115	230/208	
	Watts - Cooling	816	1020	1020/ 1000	1224	1224/ 1199	1505/ 1462	833	1263/ 1232	
	Amps - Cooling	7.8	9.8	4.6/ 5.0	11.5	5.5/ 5.9	6.9/ 7.5	7.8	5.5/ 5.9	
	Cord Length (Ft.)	7	7	6.5	7	6.5	6.5	6.5	6.5	
	Plug Type	5-15P	5-15P	6-15P	5-15P	6-15P	6-15P	5-15P	6-20P	
Dimensions	Trim Kit Dimensions (Width/Height) (in.)	27.25/17.5	27.25/17.5	27.25/17.5	27.25/17.5	27.25/17.5	27.25/17.5	27.25/17.5	27.25/17.5	
	Unit - Width/Depth/Height (inch)	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	24.12/20.3/14.5	25.5/17.5/15.25
	Carton - Width/Depth/Height (inch)	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/26.6/16.9	28/20.75/3.25
	Weight - lbs. (Net/Gross)	65/76	67/77	70/85	75/86	79/90	81/91	65/76	79/90	25/27
Loading Quantity	Pallet (84"/96")	8/10	8/10	8/10	8/10	8/10	8/10	8/10	8/10	-
	UPC code	810941021435	810941021442	810941022692	810941021459	810941021466	810941022715	810941019241	810941022708	810941019296



ECO-FRIENDLY
R-410A
REFRIGERANT

2 YEAR
Parts & Labor
Limited Warranty