




	INTERNAL BLOWER STANDARD	INTERNAL BLOWER with ACT™ AIRFLOW CONTROL TECHNOLOGY™*		
SINGLE BLOWER (INCLUDED) Min. - Max. CFM	200 - 750	200 - 590	200 - 390	200 - 290
SINGLE BLOWER (INCLUDED) Min. - Max. Sones	0.5 - 7	*AIRFLOW CONTROL TECHNOLOGY™ (ACT™) is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.		
DUAL BLOWER (OPTIONAL) Min. - Max. CFM	350 - 1,300			
DUAL BLOWER (OPTIONAL) Min. - Max. Sones	1 - 8			



FRONT



SIDE



BACK

ACT™ **POWERWAVE™**



Optional Wireless Remote Control

MODEL		ZRP-E36BS	ZRP-E48BS						
Stainless Steel Size		36"	48"						
BLOWER PERFORMANCE									
Included Single Blower		200-750 CFM, 0.5-7 Sones	200-750 CFM, 0.5-7 Sones						
ACT 590*		200-590 CFM	200-590 CFM						
ACT 390*		200-390 CFM	200-390 CFM						
ACT 290*		200-290 CFM	200-290 CFM						
Optional Dual Blower		350-1,300 CFM, 1-8 Sones	350-1,300 CFM, 1-8 Sones						
FEATURES									
ACT™ Technology		590, 390, 290, Single Blower Only	590, 390, 290, Single Blower Only						
Controls		Electronic LCD	Electronic LCD						
Speed Levels		6**	6**						
Auto Delay-Off		Yes	Yes						
CleanAir Function		Yes	Yes						
Directional Lighting		LumiLight LED, 6W x2	LumiLight LED, 6W x4						
Tri-Level Lighting		Yes	Yes						
Filters		Pro Baffle x2	Pro Baffle x3						
Grease Collection Tray		Yes	Yes						
Wireless Remote Control		Yes, Optional	Yes, Optional						
Recirculating Option		No	No						
Duct Cover Extension Option		Yes	Yes						
ADA Compliant		Yes (w/ remote accessory)	Yes (w/ remote accessory)						
DUCT SPECIFICATIONS									
Vertical Single Internal Blower		8" Round	8" Round						
Horizontal Single Internal Blower		NA	NA						
Vertical Dual Internal Blower		10" Round	10" Round						
Horizontal Dual Internal Blower		NA	NA						
AC POWER (Single Blower)		120V, 60Hz at Max. 5A	120V, 60Hz at Max. 5A						
AC POWER (Dual Blower)		120V, 60Hz at Max. 8A	120V, 60Hz at Max. 8A						
OPTIONAL ACCESSORIES									
Wireless Remote Control		14000005	14000005						
Dual Internal Blower		PBD-1300B	PBD-1300B						
Duct Cover Extension		Z1C-00RP	Z1C-00RP						
Stainless Steel Telescopic Backsplash		AK1716	AK1718						
Make-Up Air Kit (Single Blower)		MUA008A	MUA008A						
Make-Up Air Kit (Dual Blower)		MUA010A	MUA010A						
MOUNTING HEIGHT RANGE***		24" - 36"	24" - 36"						
WARRANTY		3 years parts, 1 year labor	3 years parts, 1 year labor						
CEILING HEIGHT		8'	8.5'	9'	9.5'	10'	10.5'	11'	12'
STANDARD DUCT COVER	Ducted Mounting Height***	24" - 28.5"	24" - 34.5"	24" - 36"	27" - 36"	33" - 36"	NA	NA	NA
DUCT COVER EXTENSION	Ducted Mounting Height***	NA	NA	24" - 29"	24" - 35"	24" - 36"	24" - 36"	24" - 36"	29" - 36"

*ACT™ only available with single internal blower.

**When ACT™ is enabled the number of fan speeds will be reduced to maximum 3 speeds.

***Mounting height refers to distance between top of a 36" tall cooking surface and bottom of hood.

ACT™ Airflow Control Technology™ (ACT™)
is an exclusive feature built into specific Zephyr hoods which can limit the maximum blower CFM to meet local code requirements.

POWERWAVE™

PowerWave™ 3-Phase Blower Technology
delivers best-in-class performance with unparalleled quiet operation. It provides more power while minimizing noise and improving efficiency. Plus, its 1,300 CFM blower option makes it the most powerful dual-internal blower on the market.

Specifications subject to change, check zephyronline.com for up-to-date information.
Zephyr Ventilation | 2277 Harbor Bay Parkway, Alameda, CA 94502 | 888.880.VENT

OCT23.0101

