## SUMMIT

# **SEH4636SS**



#### 29.5" x 35.44" x 19.69" (H x W x D)

36" wide European style convertible wall-mounted range hood in stainless steel

#### **Highlights:**

36" wide wall-mounted range hood

Versatile design for ducted or recirculating operation with a set of carbon filters included

Pre-installed 3-prong plug for fast setup

#### **Product Features:**

36" wide wall-mounted range hood	European style range hood designed to bring effective ventilation over 36" wide cooking surfaces	
Convertible design with no additional purchase necessary	Can be used for ducted venting to the outside or recirculating ventilation where no external venting is possible	
Charcoal filter set included	Two round carbon filters attach to the blower to absorb grease and odors when using the hood in recirculating mode	
Powerful ventilation	400 CFM blower to effectively remove smoke and cooking odors from your kitchen	
Cord included	Pre-installed power cord with 3-prong plug for 115V outlets	
LED lighting (bulbs included)	Includes two pre-installed LED bulbs to illuminate your cooking surface	
Adjustable height	Includes a telescoping chimney extender that allows you to adjust the overall height between 15 3/4" to 29 1/2"	
Stainless steel finish	Durable construction in an attractive style with a horizontal grain	
Intuitive controls	Touch buttons located towards the front of the hood let you adjust your ventilation and lighting as needed	

SUMMIT APPLIANCE DIVISION, FELIX STORCH, INC. | ISO 9001:2015 Certified 770 Garrison Avenue Bronx, NY 10474 USA TEL 718-893-3900 FAX 844-478-8799



## SUMMIT

#### SEH4636SS Specifications:

Nominal Height         30.0" (76 cm)           Height of Cabinet         29.5" (75 cm)           Nominal Width         36.0" (91 cm)           Width         35.44" (90 cm)           Nominal Depth         20.0" (51 cm)           Depth         19.69" (50 cm)           Door         Stainless Steel           Cabinet         Stainless Steel           US Electrical Safety         ETL           Amps         2.6           Voltage/Frequency         115 V AC/60 Hz           Weight         55.0 lbs. (25 kg)           Parts & Labor Warranty         1 Year           UPC         761101086842           Range Hood         Venting           Light         Yes           Number of Lights         2           Light Type         LED           Number of Fan Speeds         3           Maximum Air Movement         400.0 CFM           Sone Rating         10           Minimum Height         15.75" (40 cm)           Maximum Height         29.5" (75 cm)	Overview	
Nominal Width36.0" (91 cm)Width35.44" (90 cm)Nominal Depth20.0" (51 cm)Depth19.69" (50 cm)DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodVoltage/InstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Nominal Height	30.0" (76 cm)
Width35.44" (90 cm)Nominal Depth20.0" (51 cm)Depth19.69" (50 cm)DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Height of Cabinet	29.5" (75 cm)
Nominal Depth20.0" (51 cm)Depth19.69" (50 cm)DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodUVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Nominal Width	36.0" (91 cm)
Depth19.69" (50 cm)DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Width	35.44" (90 cm)
DoorStainless SteelCabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Nominal Depth	20.0" (51 cm)
CabinetStainless SteelUS Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Depth	19.69" (50 cm)
US Electrical SafetyETLAmps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Door	Stainless Steel
Amps2.6Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Cabinet	Stainless Steel
Voltage/Frequency115 V AC/60 HzWeight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	US Electrical Safety	ETL
Weight55.0 lbs. (25 kg)Parts & Labor Warranty1 YearUPC761101086842Range HoodInstallationInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Amps	2.6
Parts & Labor Warranty1 YearUPC761101086842Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Voltage/Frequency	115 V AC/60 Hz
UPC761101086842Range HoodVall-MountedInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Weight	55.0 lbs. (25 kg)
Range HoodInstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Parts & Labor Warranty	1 Year
InstallationWall-MountedVentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	UPC	761101086842
VentingConvertibleControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Range Hood	
ControlsPush ButtonLightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	hand all a Chain	
LightYesNumber of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Installation	Wall-Mounted
Number of Lights2Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)		
Light TypeLEDNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting	Convertible
Light (ypc)LightNumber of Fan Speeds3Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting Controls	Convertible Push Button
Maximum Air Movement400.0 CFMSone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting Controls Light	Convertible Push Button Yes
Sone Rating10Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting Controls Light Number of Lights	Convertible Push Button Yes 2
Minimum Height15.75" (40 cm)Maximum Height29.5" (75 cm)	Venting Controls Light Number of Lights Light Type	Convertible Push Button Yes 2 LED
Maximum Height 29.5" (75 cm)	Venting Controls Light Number of Lights Light Type Number of Fan Speeds	Convertible Push Button Yes 2 LED 3
	Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement	Convertible Push Button Yes 2 LED 3 400.0 CFM
Duct Shape 6" Round	Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement Sone Rating	Convertible Push Button Yes 2 LED 3 400.0 CFM 10
	Venting Controls Light Number of Lights Light Type Number of Fan Speeds Maximum Air Movement Sone Rating Minimum Height	Convertible Push Button Yes 2 LED 3 400.0 CFM 10 15.75" (40 cm)

### 2 Charcoal Filters Included for Recirculating Use



