## SUMMIT

# FF1DSS24



17.75" x 23.5" x 22.88" (H x W x D)

Single drawer all-refrigerator approved for residential and commercial use, built-in capable or freestanding, with digital thermostat, frost-free operation, and panel-ready stainless steel drawer with oversized front for use in 24" wide spaces

#### **Highlights:**

Commercially approved to ETL-S to NSF-7 and UL-471 standards for commercial settings

Flexible design allows built-in or freestanding use in 24" wide spaces

Panel-ready drawer allows you to create a truly custom look for your space

#### **Product Features:**

Commercially approved	ETL-S listed to NSF-7 standard and meets UL-471 for use in commercial settings	
Built-in capable	Front-breathing design allows you to build the drawer into cabinetry	
24" wide drawer front	Note: cabinet is sized at 21.5" wide, with the oversized stainless steel front panel to cover 24" wide openings	
Panel-ready drawer front	Drawer accepts an overlay panel to let you seamlessly blend the unit into an existing cabinetry design (panel dimensions: 15.6" H x 21.4" up to 24" W at 3/4" maximum thickness)	
304 grade stainless steel drawer	Drawer front and interior constructed from stainless steel for added durability and easy cleanability	
Frost-free operation	Minimum user maintenance with a fully no-frost operation system	
Digital thermostat	Electronic controls located on the top drawer ensure easy temperature management, with an external readout of Celsius or Fahrenheit	
LED lighting	Elegant LED lighting in a gentle white hue illuminates the refrigerator for an easy view of the interior	
Drawer dividers	Two dividers make it simple to organize the drawer interior	





### FF1DSS24 Specifications:

Overview				
Nominal Width	24.0" (61 cm)			
Nominal Depth	23.0" (58 cm)			
Nominal Height	18.0" (46 cm)			
Height of Cabinet	17.75" (45 cm)			
Width	23.5" (60 cm)			
Depth	22.88" (58 cm)			
Depth with Handle	24.38" (62 cm)			
Depth with door at 90°	36.13" (92 cm)			
Capacity	1.6 cu.ft. (45 L)			
Defrost Type	Frost-Free			
Door	Stainless Steel/Panel- Ready			
Cabinet	Black			
US Electrical Safety	ETL			
Canadian Electrical Safety	ETL-C			
Sanitation	ETL-S			
Energy Usage/Year	273.0kWh/year			
Amps	1.0			
Voltage/Frequency	115 V AC/60 Hz			
Weight	63.0 lbs. (29 kg)			
Parts & Labor Warranty	1 Year			
Compressor Warranty	5 Years			
UPC	761101081519			
Refrigerator Features				
Sabbath Mode	Yes			
Door Swing	Drawer			
Reversible	No			
Thermostat Type	Digital			
Fan Type	Interior and Exterior			
Refrigerant Type	R600a			
Refrigerant Amount	0.78oz.			
High Side PSI	270.0			
Low Side PSI	105.0			
Level Legs Qty	4			
Interior Light	Yes			

Sound Level	33.3 dB	
Dimensions		
Interior Height	13.0" (33 cm)	
Interior Width	16.0" (41 cm)	
Interior Depth	11.5" (29 cm)	
Compressor Step Height	7.0" (18 cm)	
Compressor Step Width	16.0" (41 cm)	
Compressor Step Depth	1.0" (3 cm)	



